



Exploded View



Front View



Rear View

Remove light fixtures without disturbing the fixed wiring.

- Detachable 3 / 4 pin ceiling rose.
- Complies with BS 6972.
- 6amp , 240 volts AC rating.
- Electrical and Mechanical connection is secured by inserting plug into socket & locking it by turning in right direction. Maximum safe working load provided 5Kg.
- Plug and Socket has 4 terminations: neutral, live, earth and Loop-in / Emergency light.
- The base plate is fixed in position by two screws direct to the ceiling or can be used with a round box
- Light fixtures can be plugged in in seconds, in absolute safety, without circuit isolation

- Product code : MS 1000 / 1001

Current rating	6 amp	Yellow
BS standard	BS 6972	Yellow
Cable size	1.5 mm ²	Yellow
Color	White	Blue
Mounting type	Ceiling	Blue
No: of pins	3 / 4	Blue
Earthing provision	Yes	Red
Maximum Load	5kg	Red



- Conforms to BS67: 1987
- Incorporates tunnel type terminals, and knockouts which accommodate 3 x 2.5mm² cables, transparent terminal block and equal length wire stripping
- Clear base and pre-cut aperture for ease of installation
- Terminal layout allows cables to be cut to even length
- Earth terminal point used for easier cable access
- Suitable for fittings of up to 5kgs. Heavier fittings must be installed using an independent support e.g. ceiling hook
- Diameter (Cover): 88mm x Depth (Cover) 29mm

Features & Benefits

Installation

Ceiling rose with a transparent base and clear terminal markings for ease of identification. Terminals are grouped in line with neutral, loop-in and earth terminals (1161 WHI)

Reliability

Fully compliant with the relevant British Standards 67 : 1987

Durability

Manufactured from the highest quality of raw materials to give a gloss finish, which is both scratch and colour fade resistant.

Product code

MS 1100

Voltage rating : 250V a.c.

Maximum rating : 6 amps

Terminal capacity : Live, neutral & earth

4 x 1.0mm² / 3 x 1.5mm² / 1 x 2.5mm²

Physical

Ambient operating temperature: -5°C to +40°C

IP rating: IP4X

SECURAA

Trailing / Multiple Sockets

TRAILING SOCKETS:

- Made from engineering plastic PC, high impact resistance.
- Fully shuttered 13A 4 / 5 / 6 gang trailing socket,
- Normal or Surge protected.
- As per BS 1363-A .
- Nickel plated brass sleeved pins and fuse protected.
- Individual on off rocker with neon lights.
- May be wall mounted or portable
- Standard 2 meter cable with plug top or without cable.

13 Amp / BS Socket



MSUK504S



MSUK503S



MSW504S



MSW503S

16 Amp / Universal Socket

13 Amp / BS Socket



MSUK206S



MSUK205S



MSUK504S



MSUK203S

16 Amp / Universal Socket



MSW906S



MSW905S



MSW904S



MSW903S

13 Amp BS / 16Amp Socket



MSUK5023S



MSUK5028S
13 Amp BS Socket

TRAILING SOCKETS:

- Made from engineering plastic PC, high impact resistance.
- Fully shuttered 16A 4 / 5 / 6 gang trailing socket,
- Normal or Surge protected.
- As per EN 1363-A .
- Nickel plated brass and fuse protected.
- Switch rocker with neon lights.
- May be wall mounted or portable
- Standard 2 meter cable with plug top or without cable.

16 Amp German Scuko Socket



MSG06SC



MSG05SC



MSG03SC



MSG03SC

16 Amp German Scuko Socket



MSG16SC



MSG15SC



MSG13SC



MSG13SC

PLUG TOP:

- Made from engineering plastic PC, high impact resistance.
- Nickel plated brass sleeved pins and fuse protected.
- Neon power warning light.
- As per relevant BS/EN standard.

13 Amp Plug



MS9528 / MS9528L

15 Amp Plug



MSV6615 / MSV6615L

13 Amp Plug



MS9548 / MS9548L



MS1310



MS8813



MS343B / MS343A

SECURAA

Adaptor / Ceiling Rose / Lamp Holder / Bed Switch / Terminal Strip

Adaptor



MS7196 / MS7296
MS7196L / MS7296L



MSN1928 / MSN1928L



MS1927 MS1928 MS1929
MS1927L MS1928L MS1929L

Travel Adaptor



MS931L

Adaptor



MS024UK / MS024G



MS1924 / MS1925 / MS1926
MS1924L / MS1925L / MS1926L

Bed Switch



MS5048L

MS5048

Lamp Holder



MSW330



MS230E / MS230B



MS210C / MS210E

Terminal Strip



MS100A12(40MM)



MS60A12(25MM)



MS30A12(16MM)



MS15A12(12MM)



MS10A12(10MM)



MS6A12(6MM)



MS3A12(4MM)

Aquaguard IP65



MS658313S



MS658313D



MS658313



MS658315S




MS658315D



MS658315

Cable Reel



DKUK136 Series
(5-10 Meters)



MSH Series
(5-10 Meters)



DKH9301



DK Series
(10-15 Meters)



DK Series
(5 Meters)